



Expression thru Innovation

GXLU Dual Channel WIRELESS

- Two discrete channels of wireless packaged in one receiver chassis.
- Compact discrete antenna that recess when not in use.
- Each channel has RF and AF indicator lights that indicate the presence of connectivity and audio source.
- UHF Frequency Operation
- Three output options on the receiver for maximum performance and flexibility of use.
 - Professional balanced XLR discrete
 - Professional balanced XLR mixed output
 - Professional ¼ inch output for easy output to a guitar amp or mixer equipped with ¼ inch input connections.
- Handheld transmitter outfitted with mute and on positions for flexibility of use.
- Battery life of >10hrs.
- Handheld transmitter features battery life indicator.
- All Bodypack systems ship with WXGTR guitar cable and WXHW condenser headworn mic included in the system.



GXLU



CAD Audio, LLC | 6573 Cochran Rd. Building 1 | Solon, Ohio 44139

cadaudio.com | 800-762-9266





Specifications

RXGXLU Receiver

Frequency Band	UHF
Frequency Response	50Hz – 18KHz
Dynamic Range	>105 dB
Sensitivity	-105 dB (12dB SINAD)
Output Connectors	(2) XLR Balanced, 1 TRS 1/4"

TXGXLUB Body Pack Transmitter

Transmit Power	10mW
Power Requirements	"AA" size alkaline or rechargeable batteries
Battery Life	>10 hours (alkaline)
Connector	Accepts TA4F-type

TXGXLUH Handheld Transmitter

Operating Principal	Dynamic Unidirectional Capsule
Sensitivity	-33 dBV (22mv) @ 1Pa
Transmit Power	10mW
Power Requirements	"AA" size alkaline or rechargeable batteries
Battery Life	>10 hours (alkaline)

GXLU Wireless Series available as:

- GXLUHH – UHF Dual Handheld wireless system
- GXLUHB – UHF Combo wireless system (includes WXHW, WXLAV)
- GXLUBB – UHF Dual Bodypack wireless system (includes [2] WXHW, [2] WXLAV)



Expression thru Innovation

CAD Audio, LLC | 6573 Cochran Rd. Building I | Solon, Ohio 44139

cadaudio.com | 800-762-9266